

graffiti-protect W91

Protection through a sacrificial layer

General

graffiti-protect W91 is a ready-to-use solution. It is wax-based and delivers high-quality protection for all porous mineral surfaces. Aqueous-based. It is easy and safe to use. Allows graffiti (felt-tip pens, sprayed graffiti) to be removed easily without altering the appearance of the material.

Reduces water absorption. Pores and capillaries are not sealed.

Water vapour permeability is barely reduced.

Applications

Well-suited for impregnation of porous masonry of all types: brick, natural stone, concrete, exposed concrete, lime sand brick, plaster.

Dosage

Use undiluted.

Instructions for use

Spray, roll or brush product on.

1 - 2 coats depending upon surface structure.

Each next coat should be applied when the impregnating agent is absorbed and the surface is no longer shiny.

Consumption

The amount of agent required depends upon the absorbency of the building material.

Examples: 0.3 kg / m² for smooth subsurfaces 0.3 to 0.50 kg / m² for rough subsurfaces

Important information

Sprayed graffiti must be removed with high-pressure jets (70 bar, hot) and brushes.

After surfaces are cleaned and dried, the spray protection should be applied again.

Always prepare a sample surface and have it evaluated by the client party responsible (shine may become darker).

The manufacturer accepts no liability for any damage resulting from the inappropriate use of this product.

Technical information

Shelf life	at least 2 years
Storage	do not store above room temperature
pH	of concentrate: 8
Ingredients	waxes, synthetic materials, water